

**SUMMARY-SHOOTING RANGE ARCHITECTURAL STRUCTURE , THE LAWRENCE
SCHOOL ,SANAWAR**

Date:-23-April-24

S. No.	Description of Works	AMOUNT
I	Supply , Erection and Transportation of PreFab material of Size 315Sqm	
II	CIVIL WORK	
III	CARPENTRY WORK & GLASS WORK	
	TOTAL (EXCLUDING GST & TRANSPORTATION)	

SPACE ACE



ARCHITECTS | PLANNERS | DESIGNERS

BOQ , SHOOTING RANGE , THE LAWRENCE SCHOOL SANAWAR				
		AMOUNT		
A	CIVIL WORK			
1	BRICKBAT COBA FILLING OF AVG. THICKNESS 200-250 MM TO RAISE FLOOR - AFTER LAYING OF SOIL PIPES, FLOOR TRAPS IS COMPLETED THE FLOOR SHALL BE COVERED WITH BRICKBAT COBA EMBEDDED MANUALLY WITH 15 20 MM WIDE JOINTS IN 20 MM THK. WATERPROOFING MORTAR 1:4 (1 CEMENT : 4 COARSE SAND)IN LAYERS UP TO THE FULL HT. OF RAISED PORTION, HAVING TOP LAYER OF 25 MM THK WATERPROOF MORTAR 1:4 (1 CEMENT : 4 COARSE SAND)USING SPECIALIZED W.P. CHEMICAL, FINISHED SMOOTH / ROUGH WITH FLOATING COAT OF NEAT CEMENT ALL COMPLETE AND AS PER SPECIFICATION.	162.00	CUFT	
2	BRICKBAT COBA FILLING OF AVG. THICKNESS 200-250 MM TO RAISE FLOOR - AFTER LAYING OF SOIL PIPES, FLOOR TRAPS IS COMPLETED THE FLOOR SHALL BE COVERED WITH BRICKBAT COBA EMBEDDED MANUALLY WITH 15 20 MM WIDE JOINTS IN 20 MM THK. WATERPROOFING MORTAR 1:4 (1 CEMENT : 4 COARSE SAND)IN LAYERS UP TO THE FULL HT. OF RAISED PORTION, HAVING TOP LAYER OF 25 MM THK WATERPROOF MORTAR 1:4 (1 CEMENT : 4 COARSE SAND)USING SPECIALIZED W.P. CHEMICAL, FINISHED SMOOTH / ROUGH WITH FLOATING COAT OF NEAT CEMENT ALL COMPLETE AND AS PER SPECIFICATION. (STAIRCASE)	280.00	CUFT	
3	PLASTERING			
	PROVIDING AND APPLYING 1:4 CEMENT PLASTER WITH TO BRICK / AEROCON MASONARY / R.C.C. WORKS IN SINGLE COAT OF AVG 12MM -15MM THICK FINISHED TO RECEIVE PLASTER OF PARIS LEVELLING COAT.(REPAIR WORK FOR CHISELED WALL FOR ELECTRICAL/PLUMBING WALL AFTER DISMANTLING)/ FLOOR)(AS PER ACTUAL)	395.00	RFT	
TOTAL CIVIL WORK				
B	CARPENTRY WORK & GLASS WORK			
1	PROVIDING AND FIXING DOOR /FIXING OF 4" X 2 1/2" HARD WOOD DOOR /50MM DOOR FRAME CHAUKHATS WITH ONE SIDE REBATE.RATE SHALL INCLUDE, MAKING AS WELL AS FIXING WITH ALL NECESSARY HARDWARE.	22.00	RFT	
2	SINGLE LEAF SOLID CORE FLUSH DOOR WITH CLEAR DOOR SIZES AS MENTIONED BELOW PROVIDING AND FIXING 45 MM TO 50 MM SINGLE LEAF SOLID CORE FLUSH DOOR FINISHED ON BOTH SIDES WITH 1.0MM THICK LAMINATE OF APPROVED SHADE. SHUTTER TO BE LIPPED ON ALL SIDES WITH 12MM THICK TEAK WOOD BEADING. RATE TO INCLUDE ALL NECESSARY HARDWARE, HANDLES, LOCK, CONCEALED / OPEN DOOR CLOSER / FLOOR SPRING ETC. AS APPLICABLE.	2.00	LSM	
*	DOOR OF SIZE - 2400MM (HT) X 900 MM (W), WITH CONCEALED DOOR CLOSER WITH VISION PANEL			
3	PROVIDING AND FIXING UPVC WINDOW RATE SHALL INCLUDE, MAKING AS WELL AS FIXING WITH ALL NECESSARY HARDWARE	272.00	SQFT	
TOTAL OF CARPENTRY WORK				

SPACE ACE

ARCHITECTS | PLANNERS | DESIGNERS

